

NEW! Now available with battery back-up for Egress applications



Laredo **LED** LMC-18



- 5000K high CRI LEDs
- 44.5w – 2038 Lumens
- Long Life – 50,000 hours
- IDA compliant – no uplight
- Battery back-up option for egress applications
- Die-cast aluminum housing and door with distinctive decorative ribs
- Superior performance
 - 4 to 1 spacing to mounting height ratio
 - 3 to 1 max to min footcandle levels
- Five standard finishes: Bronze, Black, Gray, White and Platinum
- Listed to UL1598 for use in wet locations
- Part of the Southwest Series design & build outdoor lighting solutions

Quick Mounting



Quick mount – easy mounting without opening fixture. Attach adapter plate to wall, connect wires, hang fixture and tighten set screws.

Photo Control



Factory installed button photocontrols. Specify voltage 120/208/240/277V.

18 High Power LEDs



18 – 5000K high CRI LEDs precisely aligned with reflectors for optimal photometric performance. Provides excellent uniformity and 4 to 1 spacing to mounting height ratio at 12-15ft.

BOC-LED Option



External charge indicator light/test switch.



Rugged, neighbor-friendly, energy-efficient design solutions for outdoor lighting

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Hubbell Outdoor Lighting • 701 Millennium Boulevard Greenville, SC 29607 • www.hubbelloutdoor.com • 864-678-1000

Rev 4.11

ORDERING INFORMATION ON REVERSE SIDE

Laredo LED LMC-18 Applications



Healthcare



Education



Office/Warehouse

The LMC 18 LED Laredo is designed for perimeter illumination for safety, security and identity. Typical mounting height is 12 to 15 feet and units can be powder paint finished to either blend or contrast with your building façade. The optical design provides wide spacing capability requiring fewer fixtures on new construction LMC or increased uniformity on retrofit applications.

Key product features include:



- 50,000 hour rated life with a minimum 70% lumen maintenance – eleven plus years in typical applications
- 5000K LED for excellent color rendition
- Wide spacing at typical 12-15ft mounting heights – 50-60ft
- No glare, IDA compliant, neighbor friendly
- Rugged die-cast aluminum housing and door with tempered clear glass lens protects the LED system
- 'Quick Mount' adapter allows one person installation without ever opening the luminaire; Adapter mounts to wall box and after wiring connections are made, fixture is secured to the adapter
- Photocontrol option provides energy saving, automatic on/off for dusk-to-dawn lighting
- Five year limited warranty provides assurance for your lighting investment

ORDERING INFORMATION (EXAMPLE)

LMC	-	18LU	-	5K	-		-	PC(4)
Laredo LMC LED	SERIES	LEDS / SOURCE / VOLTAGE	COLOR TEMPERATURE	FINISH	OPTIONS			
LMC Laredo Medium Cut-off	18LU 18 LEDs, 2038 lumens, 44.5w input	5K Nominal 5000K High CRI	1 Bronze 2 Black 3 Gray 4 White 5 Platinum	PC(X) Button photocontrol, replace X with voltage, specify 1-120V, 2-208V, 3-240V, 4-277V BOC-LED(X) Battery back-up for egress, typical mounting is nine feet, specify 1-120V or 4-277V				

Application Template
12 Ft. Mounting Height

Photometric File
LMC-18LU-5K.IES



BOC Application Template
9 Ft. Mounting Height
10 Ft. Grids

Photometric File
LMC-18LU-5K-BOC.IES

