



Outdoor Lighting

Laredo LMC New LED



- 5000K high CRI LEDs
- 44.5 Watts – 2039 Lumens
- Long Life – 50,000 hours
- Full Cutoff – IDA Compliant
- Die cast aluminum housing and door with distinctive decorative ribs
- Superior Performance
 - 4 to 1 spacing to mounting height ratio
 - 3 to 1 max to min footcandle levels
- Five standard finishes: Bronze, Black, Gray, White and Platinum
- CSA certified to UL1598 for use in wet locations
- Part of the Southwest Series design & build outdoor lighting solutions



Quick Mounting



Quick mount – easy three step mounting without opening fixture. Attach adapter plate to wall, connect wires, hang fixture and tighten set screws.

Photo Control



Factory installed button photocontrols. Specify voltage 120/208/240/277.

18 High Power LEDs



18 – 5000K high CRI LEDs precisely aligned with reflectors for optimal photometric performance. Provides 4 to 1 spacing at a mounting height of 10-15ft.

Polycarbonate Shield



1/8" clear polycarbonate, protects lens and LEDs from vandalism. Field installed.



Rugged, neighbor-friendly, energy-efficient design solutions for outdoor lighting

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Hubbell Outdoor Lighting • 701 Millennium Boulevard Greenville, SC 29607 • www.hubbelloutdoor.com • 864-678-1000

Rev 7.10

ORDERING INFORMATION ON REVERSE SIDE

Laredo LMC New LED Applications



Healthcare



Education



Office/Warehouse

The LMC LED Laredo is designed for perimeter illumination for safety, security and identity. Typical mounting height is 10 to 15 feet and units can be powder paint finished to either blend or contrast with your building façade. The optical design provides wide spacing capability requiring fewer fixtures on new construction or increased uniformity on retrofit applications.

Key product features include:

- 50,000 hour rated life with a minimum 70% lumen maintenance – eleven plus years in typical applications
- Neutral white 5000K LED color for excellent color rendition
- Wide spacing at typical 10-15ft mounting heights – 50-60ft
- No glare, full cutoff distribution, meets strict lighting codes for light trespass
- Rugged die cast aluminum housing and door with tempered clear glass lens protects the LED system
- ‘Quick Mount’ adapter allows one person installation without ever opening the luminaire, adapter mounts to wall box and after wiring connections are made, fixture is secured to the adapter
- Photocontrol option provides energy saving, automatic on/off for dusk-to-dawn lighting
- Five year limited warranty provides assurance for your lighting investment

ORDERING INFORMATION (EXAMPLE)


LMC - **18 L U** - **5K** - **1** - **PC(4)**

Laredo LMC LED

SERIES	LEDS / SOURCE / VOLTAGE	COLOR TEMPERATURE	FINISH	OPTIONS
LMC Laredo Medium Cutoff	18 LEDS L LED U Universal Voltage - 120-277V	5K Nominal 5000K High CRI	1 Bronze 2 Black 3 Gray 4 White 5 Platinum	PC(X) Button photocontrol replace X with voltage, specify 1-120V, 2-208V, 3-240V, 4-277V.

Application Template

10 Ft. Mounting Height



Photometric File
LMC-18LU-5K.IES

