



Outdoor Lighting

November 2007

NRG[®]-1100

Compact Full Cutoff Wallpack



New Product Introduction

Hubbell Outdoor Lighting Introduces NRG[®]-1100 Compact Full Cutoff Wallpack *StarView Compliant*

Neighbor-friendly distribution – no uplight or face brightness

The NRG-1100 wallpacks are shipped standard with a Full Cutoff, StarView compliant distribution that meets the strictest lighting codes.

Stylish and suitable for many architectural applications

The stylish soft corners provide a minimalistic appearance, allowing the unit to blend into many architectural building facades. Units are offered in dark bronze or white finishes and lamps are included for installer convenience. (Typical mounting height is eight to twelve feet.)

Comes loaded with standard features:

- Durable polycarbonate front housing, painted inside, for vandal resistance
- Die cast aluminum back housing with Lektrocote[®] protective paint finish, which provides rigid mounting and excellent heat dissipation for long electrical component life
- Tapped ½” hubs on all sides allow for surface conduit installation or field installation of button photocontrols
- Plated, heavy-gauge steel mounting bracket with bubble level provides simple and secure mounting to recessed wiring boxes
- Wattage ranges include 50/70/100 pulse start, 70/100 HPS and 42 CFL
- NRG-1100 is CSA certified to UL1598 for wet location applications

Please Note: 100-watt pulse start and 42-watt CFL units are sold in self-sell “ExpressLine” cartons for high visibility and qualify for the extra benefits awarded to ExpressLine program members.

See reverse side of this flyer for detailed specification sheet.

Jess Wilkerson - Hubbell Outdoor Lighting

FULL CUTOFF WALLPACK

NRG®1100 SERIES

Cat. #		Approvals
Job	Type	



APPLICATIONS

- Use for wall perimeter or entry at mounting heights of 8-15 feet. The StarView compliant optics allow no up light, saving energy and keeping the neighbors happy!

SPECIFICATIONS



- The decorative styling is also rugged with one piece polycarbonate front, painted bronze or white on the inside, that resists rocks and other small projectiles.
- The die cast housing provides rigid mounting, conduit and photo-control hubs, easy mount design and heat dissipation.

LISTINGS

- CSA certified to UL 1598 for use in wet locations.



StarView.
compliant



A	B	C
11 ³ / ₄ "	9 ¹ / ₂ "	9 ¹ / ₂ "
298 mm	241 mm	241 mm

ORDERING INFORMATION

Catalog Number ¹	Wattage/Voltage	Finish	Weight lbs. kg
PULSE START METAL HALIDE			
NRG-1111B	100 PS 120, 277, 347	bronze	12 5.4
NRG-1111W	100 PS 120, 277, 347	white	12 5.4
NRG-1171B	70 PS 120, 277, 347	bronze	11 5.0
NRG-1171W	70 PS 120, 277, 347	white	11 5.0
NRG-1151B	50 PS 120, 277	bronze	9 4.1
NRG-1151W	50 PS 120, 277	white	9 4.1
HIGH PRESSURE SODIUM			
NRG-1112B	100 HPS 120, 277, 347	bronze	10 4.5
NRG-1112W	100 HPS 120, 277, 347	white	10 4.5
NRG-1172B	70 HPS 120, 277, 347	bronze	9 4.1
NRG-1172W	70 HPS 120, 277, 347	white	9 4.1
ELECTRONIC FLUORESCENT			
NRG-1143B	42 CFL 120-277 60/50Hz	bronze	7 3.0
NRG-1143W	42 CFL 120-277 60/50Hz	white	7 3.0

¹ All fixtures include medium base or compact fluorescent lamps. Fluorescent units use universal socket and are capable of operating 26 or 32-watt PLT lamps if substituted in the field.

ACCESSORIES

(order as separate part #)

Catalog Number	Description
PBT-1	Photocontrol, button type, 120 volt
PBT-234	Photocontrol, button type, 208, 240, 277 volt

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: www.hubbell-ltg.com