



# NRG-200B Decorative Perimeter Wallpacks



## Decorative Perimeter Wallpacks – Energy Saving Motion Sensor Option

Hubbell Outdoor Lighting introduces the new NRG200B decorative perimeter wallpacks. These fixtures combine stylish curved polycarbonate design while provide lighting when people need it. The NRG-200B-MS features motion sensor controlled illumination. These units increase our solutions capability by saving energy and providing instant-on white light for commercial and residential applications.

### DESIGN STYLES

## NRG-200B Series Features & Benefits



NRG-204B



NRG-204B-MS

- Die-cast back housing provides rigid mounting and dissipates heat for long life
- Decorative curved polycarbonate front for clean appearance and vandal resistance
- 42w CFL 3500K lamp controlled by motion sensor; On only when needed
- Motion controlled unit includes sensor with 180 degree coverage
- Unit has Time-on and Sensitivity adjustments as well as a 24-hour or night only setting allowing owner to create the welcome or security lighting of their choice
- Typical mounting height up to 10ft
- Fixtures are available in multiple sources:
  - Compact fluorescent
  - Pulse start metal halide
  - High pressure sodium
- Lamps are included in all units
- Listed to UL1598 for use in wet locations



# Polycarbonate NRG-200B – Decorative Entry/Perimeter Wallpack

## ORDERING INFORMATION



NRG-204B



NRG-204B-MS

CATALOG NUMBER <sup>1</sup>		WATTAGE	VOLTAGE	COLOR	WEIGHT LBS. (KG)
Without Photocontrol	With Photocontrol				
<b>HIGH PRESSURE SODIUM</b>					
NRG-207B	NRG-207B-PC	70w	120V <sup>3</sup>	Bronze	5 (2.3)
<b>PULSE START METAL HALIDE</b>					
NRG-250B	NRG-250B-PC	50w	120V <sup>3</sup>	Bronze	6 (2.7)
<b>ELECTRONIC FLUORESCENT<sup>4</sup></b>					
NRG-204B	NRG-204B-PC <sup>2</sup>	42w	120-277V (-PC120)	Bronze	6 (2.7)
-	NRG-206B-PC <sup>2</sup>	26w	120V	Bronze	6 (2.7)
<b>MOTION CONTROLLED ELECTRONIC FLUORESCENT<sup>4</sup></b>					
NRG-204B-MS <sup>5</sup>		42w	120V	Bronze	7 (3.2)

- 1 Lamp included
- 2 120V only when ordered with Photocontrol
- 3 120V NPF ballast
- 4 CFL lamps are 4-Pin, 3500K
- 5 Motion sensor has 180° detection range, adjustable time-on and sensitivity settings

