

WALL OR CEILING MOUNT

HVL HERCULES® SERIES

Cat. #		Approvals
Job	Type	



APPLICATIONS

- For unsupervised locations where vandal resistance is a priority. HVL provides proper perspective for mounting heights from 8 to 15 feet. For either wall or ceiling mounting locations. For lower wattages, see HVS series

SPECIFICATIONS


- Opal polycarbonate lens retained with cast aluminum door/trim frame and gasketed to housing. Allan-head tamper-resistant screws standard
- Cast aluminum housing with lag mount for durability. Cast trims provide styling and added protection
- Opal lens provides a soft uniform Type V distribution. Wattage/Source selections allow the designer to select the desired footcandle level
- Sources include metal halide, HPS and fluorescent. Lamps must be ordered as an option if desired
- Powder paint finishes accent building trim and protect your investment. Standard colors include dark bronze, black, white and platinum

LISTINGS

- Listed to UL1598 for use in wet locations



HVL



	A	B
HVLO	13" 330 mm	9.75" 248 mm
ALL OTHERS	13" 330 mm	10.5" 267 mm

ORDERING INFORMATION

Catalog Number	Style	Wattage	Source	Voltage	Finish	
HVLO-070H8-1		Opal Lens	70	PSMH	Quad	Bronze
HVLO-100H8-1		Opal Lens	100	PSMH	Quad	Bronze
HVLO-070S8-1		Opal Lens	70	HPS	Quad	Bronze
HVLO-100S8-1		Opal Lens	100	HPS	Quad	Bronze
HVLO-226F9-1		Opal Lens	2 x 26	CFL	120-277	Bronze
HVLG-070H8-1		Guard	70	PSMH	Quad	Bronze
HVLG-100H8-1		Guard	100	PSMH	Quad	Bronze
HVLG-070S8-1		Guard	70	HPS	Quad	Bronze
HVLG-100S8-1		Guard	100	HPS	Quad	Bronze
HVLG-226F9-1		Guard	2 x 26	CFL	120-277	Bronze
HVLH-070H8-1		Hood	70	PSMH	Quad	Bronze
HVLH-100H8-1		Hood	100	PSMH	Quad	Bronze
HVLH-070S8-1		Hood	70	HPS	Quad	Bronze
HVLH-100S8-1		Hood	100	HPS	Quad	Bronze
HVLH-226F9-1		Hood	2 x 26	CFL	120-277	Bronze

Note: Above catalog numbers are Quad-Tap® (120, 208, 240, 277V) for H.I.D.; For 347V, change 8 to 6; Fluorescent units have universal voltage ballast 120-277V

Note: Above catalog numbers are finished in dark bronze; For optional finishes, change 1 to 2-black, 4-white, 5-platinum

OPTIONS - Add Suffix

Catalog Number	Description
-F(XXX)	Fusing: replace XXX with 120, 208, 240, 277, 347
-PC(XXX)	Button photocontrol: replace XXX with 120, 208, 240, 277, 347
-QSS	Standby incandescent system (less lamp)
-LP	Lamp included

REPLACEMENT PART

Catalog Number	Description
264-0398-9903	Replacement lens only for HVL units

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: www.hubbelloutdoor.com