

SHIELDED WALLPACK

NRG®31X SERIES COMPACT

Cat. #		Approvals
Job	Type	



APPLICATIONS


- Designed to reduce or eliminate lamp brightness for applications with mounting heights of 6 to 12 feet.

SPECIFICATIONS

- Lens is clear polycarbonate with recessed philips-drive stainless screws.
- Cast aluminum housing with powder coat protective finish.
- Mounts over recessed J-box by others.
- Specular reflector projects lumens out and down.
- Light trespass inhibitor allows additional field installed shielding.
- 50-70 watt HPS 120/277 volt, 50 watt MH 120/277 volt; lamp included.
- Dark bronze powder paint finish.

LISTINGS

- CSA certified to UL 1598 for wet locations.




A	B	C	D
7 1/4"	7"	5 1/2"	2 3/8"
184 mm	178 mm	140 mm	60 mm



ORDERING INFORMATION

ORDERING EXAMPLE: NRG-317



Catalog Number	Wattage	Voltage	Ballast	Weight
				lbs. kg
HIGH PRESSURE SODIUM				
NRG-311	50	120/277	AL-HPF	6.5 2.9
NRG-317	70	120/277	AL-HPF	7.5 3.4
PULSE START METAL HALIDE				
NRG-315	50	120/277	AL-HPF	6.5 2.9

NOTE: All units have dark bronze powder paint finish, 120/277 dual voltage ballasts, and include medium base lamp.
NOTE: No options or accessories available.

PHOTOMETRIC REPORTS

Catalog Number	Report #
NRG-315	HP07166.IES
NRG-317	HP07167.IES

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000
For more information visit our web site: www.hubbell-itg.com