

# CEILING MOUNT

NRG®4000 SERIES  
LUMASQUARE® II

Cat. #		Approvals
Job	Type	



## APPLICATIONS


- Building eaves, canopies, parking garages, or any application where an attractive high performance fixture is required.

## SPECIFICATIONS

- One-piece, injection-molded, clear prismatic acrylic refractor. High temperature acrylic for reduced yellowing, uniform light distribution and low glare. Fully gasketed for weatherproof/bugproof integrity. High transmittance acrylic featuring 82-84% efficiencies plus three times impact strength of standard acrylic. Stainless steel vandal-resistant screws standard.
- Rugged, die cast housing has a durable bronze Lektrocote® finish. Mounts over standard J-box and features two convenient 1/2" side hubs for surface conduit mounting.
- One-piece, hydroformed aluminum reflector, anodized for high reflectivity, fluted for even light distribution and full lamp life. Factory supplied clear medium base lamp. IES Type V square distribution. Vertical lamp reduces hot spot beneath luminaire, even at 8-10' mounting heights, for increased uniformity and vision.
- -40°F starting, 60 Hz HPS ballast available in 100, 150 watt HPF. -20°F starting HPF ballast is standard on pulse start fixtures.

## LISTINGS

- UL 1598 listed, CSA certified for wet locations.



A	B	C
14" square	8 1/8"	4 3/4
356 mm square	206 mm	121 mm



## ORDERING INFORMATION

Catalog Number <sup>1</sup>	Mounting	Wattage	Voltage	Power Factor	Power	Finish	Weight
							lbs. kg
<b>HIGH PRESSURE SODIUM</b>							
<b>NRG-413S8<sup>2</sup></b>	Ceiling/Conduit	100	Quad	HPF	Bronze	18	8.2
<b>NRG-414S8<sup>2</sup></b>	Ceiling/Conduit	150	Quad	HPF	Bronze	19	8.6
<b>PULSE START METAL HALIDE</b>							
<b>NRG-413P8</b>	Ceiling/Conduit	100	Quad	HPF	Bronze	18	8.2
<b>NRG-413P8WH</b>	Ceiling/Conduit	100	Quad	HPF	White	18	8.2
<b>NRG-415P8</b>	Ceiling/Conduit	150	Quad	HPF	Bronze	19	8.6
<b>NRG-415P8WH</b>	Ceiling/Conduit	150	Quad	HPF	White	19	8.6

<sup>1</sup> Includes medium base lamp.

<sup>2</sup> 50 Hz 220/240V available.

Quad-Tap® 120/208/240/277V

## PHOTOMETRIC REPORTS

Catalog Number	Report #
NRG-413HX (NRG-413PX)	<b>HP02922.IES</b>
NRG-414HX (NRG-415PX)	<b>HP06461.IES</b>
NRG-413SX	<b>HP02914.IES</b>

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: [www.hubbell-ltg.com](http://www.hubbell-ltg.com)