

HVS HERCULES®




Features



- Opal polycarbonate lens retained with cast aluminum door/trim frame and gasketed to housing. Allen head tamper-resistant screws standard.
- Two sizes for proper scale; cast aluminum housing with lag mount for durability. Cast trims provide styling and added protection.
- Opal lens provides a soft uniform Type V distribution. Wattage/Source selections allow the designer to select the desired footcandle level.
- Sources include Metal Halide, HPS, Fluorescent and Incandescent. Lamps must be ordered as an option if desired.
- Powder paint finishes accent building trim and protect your investment. Standard colors include dark bronze, black, white and platinum.
- Certified to UL 1598 for use in wet locations.



Ordering Information

Catalog Number	Style	Wattage	Source	Voltage	Finish	
HVSO-28F1-1		Opal Lens	28	FLUOR	120	Bronze
HVSO-42F9-1		Opal Lens	42/32/26	FLUOR	120-277	Bronze
HVSO-50S1-1		Opal Lens	50	HPS	120	Bronze
HVSO-60I1-1		Opal Lens	60	INC	120	Bronze
HVSG-28F1-1		Guard	28	FLUOR	120	Bronze
HVSG-42F9-1		Guard	42/32/26	FLUOR	120-277	Bronze
HVSG-50S1-1		Guard	50	HPS	120	Bronze
HVSG-60I1-1		Guard	60	INC	120	Bronze
HVSH-28F1-1		Hood	28	FLUOR	120	Bronze
HVSH-42F9-1		Hood	42/32/26	FLUOR	120-277	Bronze
HVSH-50S1-1		Hood	50	HPS	120	Bronze
HVSH-60I1-1		Hood	60	INC	120	Bronze

Note Above catalog numbers are finished in dark bronze. For optional finishes, change 1 to 2-black, 4-white, 5-platinum.
 Note HID and Incandescent sockets are medium base.

Options - Add Suffix

Catalog Number	Description
-LP ¹	Lamp included.


1 42 watt fluorescent lamp shipped when ordered with 42F9 fixtures.

Replacement Part

Catalog Number	Description
264-0400-9903	Replacement Lens only for HVS units

Dimensions

HVS



	A	B
HVSO	10 1/10"	5"
	257 mm	127 mm
All Others	10 1/10"	5 1/2"
	257 mm	140 mm